

Magnetic Scale Reducer 15mm Compression

58264

- An in-line scale reducer to prevent the build-up of scale using magnetic principles
- Single appliance protection
- A brass, nickel plated unit
- Lasts for up to 10 years
- WRAS approved product
- No need for an earth bond strap



The Fernox Magnetic Scale Reducer range is suited to single appliance protection and is most notably used to protect the boiler against the damaging effects of scale. It is easily connected onto 22 mm pipework and requires no further maintenance, while the positive effects continue for up to 10 years, dependent on water usage levels. Part L of the Building Regulations (England and Wales) states that in hard water areas which exceed 200ppm, provision should be made to treat feed water to water heaters and hot water circuits of combination boilers to reduce the rate of limescale formation as well as limiting its harmful effects on energy efficiency

Application

The Fernox Magnetic Scale Reducer is installed into the pipework using pushfit fittings. In an average domestic household, the Fernox Magnetic Scale Reducer provides single appliance protection. The unit is effective immediately and is guaranteed for 12 months against manufacturing defects. The unit is pressure rated to 10 bar at 20 °C with an operating temperature of 2 °C to 40 °C (cold feed) and is designed for 22mm pipework. Install in compliance with WRAS installation requirements IRN R001, R120, R150, R170, R290 and/or local water regulations.

Package, Handling & Safety

The Fernox Magnetic Scale Reducer can be installed in horizontal or vertical pipework. The unit is classified as non hazardous, but magnets may affect or interfere with sensitive mechanical and electronic instruments such as heart pacemakers, computers, magnetic media and watches. Always keep magnets at least 300mm (1 foot) away from such devices.

Specification

Material: Forged Brass, Chrome Plated

Visit [Plumb2u](#)

See product

Copyright Fernox ©

Single Item

Height mm 40
Width mm 182
Depth mm 39
Weight kg 0.560
Barcode EAN 5014551582644

Outer Carton

Outer Height mm 200
Outer Width mm 221
Outer Depth mm 90
Outer Weight kg 5.040
Transit Type Euro 1200 x 800
OCU Barcode 05014551000018

Last modification 25-02-2021 (d/m/y)

[Visit Plumb2u](#)

[See product](#)