

DECLARATION OF PERFORMANCE

No. BB1503L/2025

1. *Unique identification code of the product-type:*

LIGNOFOL® 300 DAMP-PROOF MEMBRANE

2. *Intended use/es:*

Flexible sheets for waterproofing. Damp proof sheet.

3. *Manufacturer:*

ERG BIERUŃ Sp. z o. o.
ul. Chemików 163
43-150 Bieruń

4. *System/s of AVCP:*

system 2+ and system 4 for reaction to fire

5. *Harmonised standard:*

EN 13967:2012 Flexible sheets for waterproofing – Plastic and rubber damp proof sheets including plastic and rubber basement tanking sheet – Definitions and characteristics.

Notified body/ies:

No. UK 0836 British Board of Agreement Bucknalls

6. *Declared performance/s:*

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to the fire	class F	EN 13967:2012
Water tightness	Pass at 2 kPa	
Resistance to tearing (nail shank)	$\geq 100 \text{ N} / \geq 100 \text{ N}$	
Joint strength	NPD	
Resistance to impact	$\geq 200 \text{ mm}$	
Tensile properties: Tensile force: along/across Elongation: along/across	$> 100 \text{ N}/50\text{mm} / > 80 \text{ N}/50\text{mm}$ $> 350\% / > 350\%$	
Resistance to static loading	NPD	
Durability: - against ageing/ degradation - against chemicals	Pass at 2 kPa Pass at 2 kPa	
Dangerous substances	NPD	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Barbara Filipczyk – Quality management representative
Bieruń, 1.09.2025

